

THE #1 NAME IN BATTERY CHARGERS
AROUND THE WORLD.

 Schumacher®



// BATTERY CHARGERS



// JUMP STARTERS



// BATTERY TESTERS



// WORKLIGHTS



PRODUCT CATALOGUE
2019-2020

02

shumacher



// PASSION FOR TECHNOLOGY.

Since 1947, **Schumacher Electric Corporation** has been leading change and driving performance to exceed its customers' expectations. Engineered patent-pending technologies and award-winning marketing makes Schumacher the brand of choice. Schumacher's legacy is its commitment to quality and exceptional customer service. Schumacher brings experience, innovation and excellence to the next generation of battery maintenance... the #1 name in battery chargers around the world.



Don Schumacher




Evolution of the Schumacher brand through the years.

The Schumacher name is also synonymous with NHRA drag racing. Don Schumacher rocked the racing world with his driving abilities and in 2013 Don was inducted into the International Motorsports Hall of Fame. Now his son, Tony Schumacher, is rocking the driving world with his eight consecutive NHRA Top Fuel World Championships. Passion and commitment are the Schumacher way.



// COMMITMENT TO QUALITY.

Headquartered in the Illinois, Schumacher Electric Corporation is the leader on the US market of battery chargers. The company also develops various tools of power conversion for private and professional users. The group Schumacher Electric Corporation consists of 7 production, distribution and R&D locations worldwide, among which Schumacher Europe's (formerly known as Ceteor Sprl) premises in Harzé, situated in the Belgian Ardennes. Thanks to the union of Schumacher Electric and Ceteor SPRL, the group strives to be the world leader in the manufacture and distribution of battery chargers and boosters for all types of vehicles.



USA - MOUNT PROSPECT

// Schumacher Global Headquarters

USA - DALLAS

// Distribution center

MEXICO - MATAMOROS • Schumex

// Factory

CHINA - BINHAI • Schumacher China

// Factory

CHINA - SUZHOU • DST

// design and engineering center

BELGIUM - HARZE • Schumacher Europe

// EU Headquarters // Factory // Distribution center

ITALY - PIEVE DEL GRAPPA • Electromem

// Headquarters // Factory // Distribution center

AUSTRALIA - QUEENSLAND • Schumacher Asia Pacific

// Distribution center



BATTERY CHARGERS

SPI SERIES.....8-9
CHARGER ACCESSORIES.....10
INDUSTRIAL CHARGERS.....11



JUMP STARTERS

HYBRID - ULTRACAPACITOR TECHNOLOGY.....12
LITHIUM-ION TECHNOLOGY.....13
AGM TECHNOLOGY.....14-15



BATTERY TESTERS16



WORKLIGHTS.....17-22



Meets the Highest Industry Standards
for Energy Efficiency



POWERED BY SCHUMACHER

Charge and maintain your battery for less than 1€ a year.



Schumacher Electric Corporation offers many energy-efficient products. We recognize the importance of supporting long-term ecological balance. We further commit to this by implementing our Sustainability Initiative.



**MAXIMIZING
ENERGY EFFICIENCY**
SUPERIOR PERFORMANCE

SPI SERIES: FASTER, SMARTER, SAFER & ECO-FRIENDLY
Fully automatic & microprocessor-controlled



Patented Speed Charge Technology ensures that the battery is charged as fast and safely as possible – up to 3 times faster than traditional chargers. **Designed to charge most types of batteries (AGM, Gel, Calcium/Wet, Start & Stop).**

The SPI3 is also compatible with lithium-ion batteries. The range features a digital display with scrolling multilingual instructions (except SPI1 & SPI2) insulated clamps and eyelet accessories (except SPI15 and SPI1224V), a hook attachment and protection bumpers.

Reverse polarity protection, thermal runaway protection and automatic shut-off are included as standard. The SPI will charge batteries with voltage as low as 0.5V. In comparison, most chargers from the competition will only charge batteries with voltage as low as 4V. Their ventilated housing compensates for the extra heat and prolongs the life of the chargers. The SPI are energy efficient and meet the highest industry standards. They feature multi-stage charging for added precision and safety. Float-mode monitoring ensures that the battery is kept fully charged and ready to use, for extended periods of time.

	SPI1	SPI2	SPI3	SPI6	SPI10	SPI15	SPI1024	SPI1224
Part number	94065104C	94065049C	94065050C	94065091C	94065092C	94065189C	94065119C	94065194C
DC Voltage	6/12V		12V			24V		12/24V
Nominal AC voltage	230V AC - 50 Hz							
Max. charging current	1A	2A	3A	6A	10A	15A	10A	15A/10A
Dimensions (mm)	145 (L) x 90 (W) x 45 (H)	193 (L) x 84 (W) x 78 (H)	194 (L) x 89 (W) x 83 (H)	183 (L) x 140 (W) x 60 (H)	183 (L) x 140 (W) x 60 (H)	203 (L) x 156 (W) x 74 (H)	203 (L) x 156 (W) x 74 (H)	203 (L) x 156 (W) x 74 (H)
Weight	0,40 KG	0,65 KG	0,78 KG	1,20 KG	1,20 KG	1,25 KG	1,25 KG	1,45 KG
IP rating	IP54	IP54	IP64	IP20				
Working t°	-20° to +50° C							

SPI1
6/12V-1A Maintainer

- For 6/12V batteries up to 32Ah
- Automatic voltage detection
- Charging status LEDs



SPI2 6/12V-2A Battery Charger/Maintainer

- For 6/12V batteries up to 32Ah
- Automatic voltage detection
- Charging status LEDs



SPI3 12V-3A Battery Charger/Maintainer

- For 12V batteries up to 58Ah
- Scrolling digital display
- Compatible with Lithium batteries (LiFePO4)



SPI6 12V-6A Battery Charger

- For 12V batteries up to 130Ah
- Scrolling digital display
- Ventilated housing



SPI10 12V-10A Battery Charger

- For 12V batteries up to 200Ah
- Scrolling digital display
- Ventilated housing




SPI15 POWER SUPPLY 12V-15A Standard mode 12V-10A Power supply mode

- Especially designed to charge 12V batteries of vehicles sitting idle in a showroom
- For 12V batteries up to 230Ah
- Scrolling digital display
- Ventilated housing



SPI1024 24V-10A Battery Charger

- For 24V batteries up to 200Ah
- Scrolling digital display
- Ventilated housing



SPI1224 12V-15A Standard/Recovery mode 24V-10A Standard/Recovery mode

- For batteries 12 and 24V up to 230Ah
- Scrolling digital display
- Ventilated housing



CHARGER MOUNTING PLATES

Mount your SPI Chargers on a wall

SA190

Compatible with SPI6 & SPI10

Part Number 94065151

SA191

Compatible with SPI15 Power supply, SPI1024 & SPI1224

Part Number 94065152



BATTERY INDICATOR CABLE

Check the state of charge of your batteries at a glance

SA831 Battery Indicator 12V

Part Number 94500831

- Compatible with: SPI1, SPI2, SPI3, SPI6, SPI10
- Cable length: 65 cm
- Includes a replaceable 15Amp in-line fuse
- Fitted with M8 eyelets



3 METER EXTENSION CORD

Extend the range of your charger

SA857 Extension cord

Part Number 94500857

- Extend the range of your charger
- Compatible with SPI1, SPI2, SPI3, SPI6, SPI10, SPI1024
- The cable is fitted with Schumacher quick-connect on both sides
- Cable length : 300 cm - Cable cross-section : 1.3mm² / AWG 16



ACCESSORIES



- Eyelet Cord w/ 7.5A in-line fuse

Part Number 2299002042

- Clamp Cord 18GA

Part Number 3899002636

Compatible with:
SPI1, SPI2, SPI3, SPI6

- Eyelet Cord w/15A in-line fuse

Part Number 3899003531

- Clamp Cord 16GA

Part Number 3899003431

Compatible with:
SPI10, SPI1024



- Cigarette-lighter Connector Cord

Part Number 94065149

Compatible with all chargers up to 10A



INC100

12V-100A Battery Charger / Power Supply

Part Number 94065033C (EU PLUG)
Part Number 94065033G (UK PLUG)

Charge, maintain and support batteries during diagnostic work

Fully automatic & microprocessor-controlled battery charger for batteries of any size: lead-acid, AGM, calcium, start/stop & Gel.

Three selectable modes:

- Automatic: up to 70A charging current
- Manual: variable charge rates (4/20/70 Amps) and digital timer
- Flash Reprogram: maintains stable voltage under varying loads during ECU reprogramming and diagnostic work. Voltage can be set between 13.0-14.8V. Features 70A continuous and 100A Peak (3 minutes) output current. Can also be used to maintain the battery of vehicles sitting in Showrooms.



Recovery mode for deeply discharged & sulphated batteries included

Digital display shows voltage and output current

5-meter cables equipped with heavy-duty clamps and Anderson connector

Adjustable mounting brackets for permanent installation to most vehicle lifts

Durable aluminum case

Dual temperature-controlled cooling fans

Short-circuit and thermal runaway protection

Case dimensions (LxWxH): 324 x 108 x 235mm



SCI90

6/12V-90A Battery Charger with Engine Start Mode

Part Number 94065007C

Extend the life of your batteries with this multifunction charger

Fully automatic microprocessor-controlled charger

Automatic voltage detection (6/12V)

Battery type selection between AGM, Gel, Calcium and sulfated batteries.

Charge rate selection: Slow (3A), Medium (5A) and Fast (20A)

90A / 150A Peak Engine Start mode for emergency starting

Built-in digital voltmeter/tester – shows battery voltage & charging percentage

Helps diagnose problems

175cm output cables with cord wrap on the back of the unit

Reverse polarity, short-circuit and thermal runaway protection

Case dimensions (LxWxH): 232 x 258 x 171 mm

Weight: 5.82 kg



SCHUMACHER 12V HYBRID BOOSTERS 12V-900A – 1200A

Hybrid 12V-900A - Part Number 310900
Hybrid 12V-1200A - Part Number 311200

- Ultracapacitor jump starters with back-up lithium battery.
- Ultra compact and 3 times lighter than traditional AGM jump starters.
- Three ways of precharging the internal capacitors:
 - 1) From vehicle's flat battery (60-120 sec)
 - 2) On-board a vehicle via the 12V cigarette-lighter cable (4-6 min)
 - 3) With the internal lithium battery (4-6 min)
- Digital display shows vehicle's battery voltage and charging level of internal capacitors
- Features: heavy-duty clamps, 90cm flexible cable, and a shock-absorbing rubber protection
- Comes with a 12V cigarette-lighter cable and a Micro-USB cable to charge the lithium battery



SCHUMACHER 12/24V HYBRID BOOSTER 12/24V-1500/750A

Part Number 311500

- 12/24V Ultracapacitor jump starter with back-up lithium LiFePO4 battery
- Can start all types of vehicles, including trucks and busses
- Only 11 kg – 2 times lighter than a traditional 12/24V jump starter
- Features: 1,70 meter flexible cables and heavy-duty clamps
- Equipped with a rotary switch to select voltage,
- LCD display shows vehicle battery voltage and charging level of internal capacitors
- Two ways of precharging the internal capacitors:
 - From vehicle's flat battery
 - With the internal lithium battery



MODEL	VOLTAGE (DC)	CRANKING AMPS (CA)	PEAK AMPS (PA)	CABLE LENGTH	WEIGHT	DIMENSIONS L x h x w (mm)
Hybrid 12V-900A	12V	900	1800	0,90 m	2,8 kg	235 x 230 x 155
Hybrid 12V-1200A	12V	1200	2400	0,90 m	3,0 kg	235 x 230 x 155
Hybrid 12/24V - 1500/750A	12/24V	1500/750A	3000/1500	1,70 m	11 kg	230 x 430 x 430

MODEL	GASOIL ENGINES		DIESEL ENGINES		
	WARM NO BATTERY	COLD NO BATTERY	WARM NO BATTERY	COLD LOW BATTERY	COLD NO BATTERY
Hybrid 12V-900A	<8.0L	<6.0L	<4.0L	<4.0L	<3.0L
Hybrid 12V-1200A	<8.0L	<7.0L	<5.0L	<5.0L	<3.5.L
Hybrid 12/24V - 1500/750A	<8.0L	<7.0L	<7.0L	<6.0L	<5.0L

JUMP STARTERS // HYBRID - ULTRACAPACITOR TECHNOLOGY



SLI2 PROFESSIONAL LITHIUM BOOSTER

Part Number 94065205C

Jump Start up to 50 vehicles in a row

- Super Light, compact and powerful jump starter
- Long-lasting & high-output Lithium LiFePO4 battery (24,000 mAh)
- Features a scrolling display with step-by-step instructions
- Dual 2.1A USB Ports to charge smartphones & tablets
- Heavy-duty curved clamps and flexible cable
- Comes with a 12V-3A automatic & intelligent charger and a 12V cable for on-board charging
- 12V port adapter to power 12V devices and to use as a memory saver
- Fully safe & automatic: Spark-free protection against reverse polarity, overcurrent, short-circuit, overload, overvoltage and overcharge
- The SLI2 is capable of starting 5L petrol and 3.6L diesel engines



SCHUMACHER LITHIUM-ION POWER PACKS

Great for starting vehicles in emergencies and charging portable electronics

SL1327U

800 Peak Amp Power Pack

Part Number 9402613271



SL1317U

1000 Peak Amp Power Pack

Part Number 9402613171



SL1327U

SL1317U

COMPACT DESIGN

Strong and durable enclosure design with premium soft-touch coating. It fits conveniently in your travel bag.

JUMP STARTER

Quickly starts 12V vehicles in emergencies – both petrol and gasoline

POWER PACK

Multiple Output Ports make charging mobile devices faster and more efficient:

- Fast USB 5V, 2.4A to charge USB based mobile devices
- Faster Charge Qualcomm® Quick Charge™: 3.0 to charge USB based mobile devices

BACKLIT LCD DISPLAY WITH ON/OFF BUTTON

LCD display with backlight to show battery capacity, in/output activities and errors

SMART CABLE

Provides protection against reverse polarity, short circuit, low voltage, high temperature and reverse charging. Safety built-in the main unit.

BUILT-IN LED LIGHT

(3 Modes)

PBI1812 Booster 12V



Part Number 94065001C

- Professional high-output AGM battery
- ON/OFF switch eliminates shorting of clamps & battery drain
- Reverse polarity alarm
- Colour LEDs indicate battery level and charging status
- 300A in-line fuse protects against excessive current output
- 12V accessory outlet, also used for memory saver mode
- External 700mA automatic charger
- Lightweight, compact & durable case
- Anti-spiking protection



PBI200 Booster 12V Premium



Part Number 94065200C

- Professional 900CA high-output AGM battery
- ON/OFF switch eliminates shorting of clamps & battery drain
- Reverse polarity alarm & anti-spiking protection
- Digital display indicates internal battery level and voltage of vehicle's battery
- Heavy-duty curved clamps & flexible cable
- 300A in-line fuse protects against excessive current output
- 12V accessory outlet - also used for memory saver mode
- External 12V-2A automatic & intelligent charger
- 2,1A USB output ideal for charging smartphones & tablets



PBI201 Booster 12/24V Premium



Part Number 94065201C

- 2 x professional 900CA high-output AGM batteries
- ON/OFF switch eliminates shorting of clamps & battery drain
- Reverse polarity alarm & anti-spiking protection
- Digital display indicates internal battery level and voltage of vehicle's battery
- Heavy-duty curved clamps & flexible cable
- 500A in-line fuse protects against excessive current output
- 12V accessory outlet - also used for memory saver mode
- External 12V-2A automatic & intelligent charger
- 2,1A USB output ideal for charging smartphones & tablets



PART NUMBER	MODEL	VOLTAGE (DC)	CRANKING AMPS (CA)	PEAK AMPS (PA)	CABLE LENGTH	CABLE CROSS SECTION	AUTOMATIC CHARGER	NET WEIGHT	DIMENSIONS
94065001C	PBI1812	12V	700	2200	0,71 m	21 mm ²	1,3 A	7,5 kg	31 x 28 x 12
94065200C	PBI200	12V	900	2300	1,59 m	21 mm ²	1,3 A	10,0 kg	31 x 34 x 13
94065201C	PBI201	12/24V	1800/900	4600/2300	1,70 m	33 mm ²	1,3 A	19,1 kg	37 x 37 x 21
232008	PBI2400	12/24V	2400/1200	6200/3100	1,52 m	50 mm ²	4A	31 kg	45 x 57 x 29

PBI2400 HD Booster 12/24V

Part Number 232008

For 12V and 24V vehicles – can start diesel engines up to 1500HP Features:

- 2 x professional 1200 CA high output AGM Batteries
- Rotomolded and unbreakable housing
- Retractable handle
- Puncture-proof wheels
- Double-insulated and ultra-flexible 50mm² cable
- Heavy-duty curved clamps
- Anderson connectors for voltage selection (12/24V)
- Reverse polarity buzzer
- 500A fuse for short-circuit protection + 1 spare fuse
- 12V cigarette-lighter socket to use booster as a power source or memory saver
- Optional: auxiliary connector for auxiliary cables



JUMP STARTERS //
AGM TECHNOLOGY



OBD-L Memory Saver Detector Cable

Part Number 940261086

Save the settings of your vehicle while disconnecting and replacing the battery

Attach the OBD-L between a portable power unit (PBI or Ceteor Booster for example) and the vehicle's OBDII diagnostic port. This allows to maintain power to the vehicle's on-board devices when the vehicle's battery is disconnected for service or replacement. Fully automatic and user-friendly. Works on all vehicles equipped with a standard OBDII port. Colour LED indicate if the connection on both sides is OK, and if it is safe to disconnect the battery.



SBT1

Schulink Wireless Tester for 6/12V batteries & 12/24V charging systems

Part Number 940261243



Perform battery and system test wirelessly from your smartphone or tablet
You can then send the results by email or text messages.

- Works with Bluetooth connection and the SBT1 Schulink app (available on iOS & Android) which includes 8 languages
- Application: 6 & 12V automotive batteries (SS, EFB, Start-Stop, AGM and EV batteries included), as well as 12 & 24V charging/starting systems
- Able to test all types of lead-acid batteries as low as 1.5V and with 40-2000CCA operating range
- Stores up to 2.000 test records
- Compact design with waterproof (IP65) rating
- 3.7V internal lithium ion battery to enable testing of batteries with low voltage
- Product dimensions (LxWxH): 98 x 50 x 25 mm
- Weight: 0.32 kg



PTI900X

Part Number 94065027

- Application: 6 & 12V batteries and 12 & 24V charging/starting systems
- Compatible with all types of lead-acid batteries
- Voltmeter range: 1.5V-30V
- Operating range: 40-2000CCA (SAE)
- Built-in thermal printer and LCD display
- Comes in heavy-duty plastic case and includes 6 x AA batteries and a paper roll
- Case dimensions (LxWxH): 251 x 130 x 64 mm
- Weight: 1.5 kg



SBT Smart Battery Tester

Part Number 410000

- Application: 6 & 12V batteries and 12 & 24V charging/starting systems
- Compatible with all types of lead-acid batteries, including Start-Stop
- Voltmeter range: 1.5V-30V
- Operating range: 40-2000CCA (SAE)
- Built-in thermal printer and LCD display
- Comes in heavy-duty plastic case and includes 4 x AA batteries and 2 paper rolls
- Detachable cables – easy to replace
- Case dimensions (LxWxH): 310 x 200 x 90 mm
- Weight: 1.5kg



BT175

Digital Tester for 12V batteries & starting/charging systems

Part Number 940261128



- For Lead-Acid, VRLA, AGM and Gel Batteries
- Digital display shows voltage and CCA rating
- LED lights indicate diagnostic (OK – OK & Recharge – Recharge & Retest Weak – Bad Battery)
- Voltmeter range: 7-15V
- Operating range: 100-1200CCA (SAE)
- Dimensions (LxWxH): 70 x 120 x 15 mm
- Weight: 0.25 kg

BT55U

6/12V Voltmeter and Alternator Tester

Part Number 940261175



- Checks the battery state of charge and charging system output.
- Easy-to-read LCD display
- Two LED indicators show the status of the alternator
- Dimensions (LxWxH): 70 x 120 x 15 mm
- Weight: 0.20 kg

SL 876U
Flexible worklight



SL 26
200 Lumens worklight 360°

Part Number 140001

- 5 Super bright SMD LED + 1 watt torch function
- Soft touch rubberized casing
- Multifunction switch for worklight and torch
- End mounted super strong magnet
- Swivel hook
- Micro USB charging cable included



SL 28
300 LUMENS WORKLIGHT 360°

Part Number 140002

- Li 2200 mAh battery
- 300 lumens 210 min Life - 150 lumens 420 min Life
- 7 Super bright SMD LED + 3 watt torch function
- Soft touch rubberized casing
- Multifunction switch for high/low and torch function
- Two rear and end mounted super strong magnets
- Two swivel hooks
- Micro USB wall charger included



SL 360
400 Lumens worklight 360°

Part Number 140003

- Li 2200 mAh battery
- 400 lumens 180 min Life - 200 lumens 360 min Life
- 10 Super bright SMD LED + 3 watt torch function
- Soft touch rubberized casing
- Multifunction switch for high/low and torch function
- One base and two rear mounted super strong magnets
- Two swivel hooks
- Micro USB cable included



SL 137

600 Lumens worklight 360°

Part Number 140005

- Li 2x 2600 mAh batteries
- 600 lumens 360 min Life - 300 lumens 720 min Life
- 3 LED battery level Indicators
- 16 Super bright SMD LED + 3 watt torch function
- Multifunction switch for high/low and torch function
- One base and two rear mounted super strong magnets
- Two swivel hooks
- Micro USB charging cable included



SL 136

Colour match worklight 360°

Part Number 140004

- Li 2600 mAh battery
- 400 lumens 150 min Life - 200 lumens - 270 min Life
- Especially designed for colour match and paint industry
- Provides superior color rendering (CRI 95)
- Soft touch rubberized casing
- Built-in fan for longer bulb life
- Battery Status LED on back indicate battery level
- End mounted super strong magnet
- Swivel hook
- Micro USB charging cable included



SL 184

SLIM worklight 360°

Part Number 140010

- Li 2600 mAh battery
- 600 lumens 120 min Life
- 16 Superbright SMD LED
- Soft touch rubberized casing
- Adjustable rotary switch - up to 600 lumens
- Unique 360° swivel and tilt function
- Magnetic base
- Retractable hook
- Micro USB charging cable included



SL 197U Toolbox Worklight

Part Number 140011U

Perfect for lighting up toolboxes, cabinets and work stations.
Sliding magnetic brackets rotate 180°.

- 15 SMD LEDs, 6500K, 80+ CRI
- Two brightness settings (Low/High)
- Two 180° rotatable adjustable magnetic brackets
- Durable aluminum housing
- PC lens to protect user's eyes
- With Micro/USB to USB charging cable
- Rechargeable Lithium Ion battery: 3.7V – 2.2Ah
- Battery Status LED Indicator : red for charging, green for charged
- IP20, IK07



SL 876U Flexible worklight

Part Number 94500876

Super flexible light is impact and water-resistant.
Has beam-focusing system with spotlight or wide area options.

- Cree® XPG High-Performance LED
- 250 Lumen
- Magnetic base
- With Micro/USB to USB charging cable



SL 879U Floor lamp with replaceable battery

Part Number 94500879

- 15W COB LED, up to 1200 Lumens
- Stepless dimmer mode
- Battery level indicator LEDs
- Floor Lamp with Replaceable Battery
- 15W COB LED, up to 1200 Lumens
- Aluminum body
- Removable battery pack
- Rechargeable 18650 Lithium-Ion battery: 7.4V - 4Ah
- IP44

Optional accessories (sold separately):



SA882U
Tripod Stand
(for use with one
or two lights)
94500882



SA881U
Magnetic Stand
94500881



SA880U
Additional
Removable Battery
94500880z



SL 886U

RECHARGEABLE PORTABLE WORKLIGHT WITH MAGNETIC BASE

Part Number 94500886

- 600 Lumens (High setting) – 300 Lumens (Low Setting)
- Unique ball joint enables 360° swivel and tilt
- Magnetic Base and adjustable swivel hook
- Aluminum and ABS housing
- Li-ion 3.7V 2600mAh Battery
- 180 min. life (Low setting) – 90 min. life (High setting)
- Supplied with Micro-USB Cable



SL 25

LED CORDLESS EXTENDABLE WORKLIGHT

Part Number 140006

- 1 SMD 15 lumens - 8 SMD 100 lumens
- Adjustable head with 0.5W LED for use as a directional torch
- Alternatively extends out revealing 8 SMD LED for use as an inspection lamp
- Features a magnet in the end for hands-free use
- Powered by 3 Long-Lasting Alkaline AAA batteries (supplied)
- Available in Display Pack of 12 Pieces



SL 175

SWIVEL FLOOR WORKLIGHT 360°

Part Number 140007


- 750 Low lumens - 1500 Medium lumens - 3000 High lumens
- Li 4400 mAh
- 72 Super-bright SMD LED
- Soft touch foam-rubber handle
- Low/Medium/High/OFF Push button
- Unique ball joint enables 360° swivel and tilt function
- 3 battery level LED Indicators
- USB 5V2,1A outlet for charging electronics (mobile phone, tablet etc).
- IP 65
- Wall charger included



UNDERHOOD WORKLIGHT SL 176

Part Number 140008

- 400 lumens low - 1000 lumens high
- Li 2600 mAh
- Three super-bright 5W COB LED
- 60° Beam angle
- Die-cast aluminium housing with durable ABS
- COB covered with polycarbonate lens to protect user's eyes
- 40° Angle adjustable lamp heads
- Foam covered handles won't mark the paint
- LED Power indicator for battery charge level
- Adjustable length 119 to 175 cm
- Micro USB charging cable included



Part Number 143602



Part Number 143601



Part Number 000000255



Schumacher®



PERFORMANCE. INNOVATION. POWER

Schumacher Europe SPRL | Z.I - Rue de la Baronnerie 3 | B-4920 Harzé - Belgium | www.schumachereurope.com | +32 4 388 20 17